

Maverick Maintenance Log: record date in box after procedure is done.

Maintenance item	Miles/ Km of use																					
	Miles	100	200	300	400	500	600	700	800	900	1000	1100	1200	1300	1400	1500	1600	1700	1800	1900	2000	
	Kilometers	160	320	4.8K	6K	8K	9.5K	11K	12K	14.5K	16K	17.5K	19K	21K	22.5K	24K	25.5K	27K	29K	30.5	32K	
Check Mono-Link pivot bolt torque																						
Check upper shock mount torque																						
Check damper set screws torque																						
Check shock body/ super stay bolts torque																						
Check shock body/ chain stay bolts torque																						
Clean and inspect rear damper seals																						
Inspect & grease Mono-Link pivot bearings																						
Overhaul rear damper *																						

Maintenance item	Miles/ Km of use																					
	Miles	2100	2200	2300	2400	2500	2600	2700	2800	2900	3000	3100	3200	3300	3400	3500	3600	3700	3800	3900	4000	
	Kilometers	33.5K	35K	37K	38.5K	40K	41.5K	43K	45K	46.5K	48K	49.5K	51K	53K	54.5K	56K	57.5K	59K	61K	62.5K	64K	
Check Mono-Link pivot bolt torque																						
Check upper shock mount torque																						
Check damper set screws torque																						
Check shock body/ super stay bolts torque																						
Check shock body/ chain stay bolts torque																						
Clean and inspect rear damper seals																						
Inspect & grease Mono-Link pivot bearings																						
Overhaul rear damper *																						

Fastener	Torque Values	Lock-Tite? **	Grease?
Mono-Link pivot bolts	75 in./lbs. (8.5 nm)	No	Shaft, not threads
Upper shock mount bolt	75 in./lbs. (8.5 nm)	blue	Shaft, not threads
Shock body/ Super Stay bolts	75 in./lbs. (8.5 nm)	red	yes
Shock Body/ Chain Stay bolts	75 in./lbs. (8.5 nm)	red	yes
Damper set screws	15 in./lbs. (1.7 nm)	blue	yes
Front Derailleur fixing bolt	20 in./lbs. (2.3 nm)	No	No
Derailleur hanger fixing bolt	25 in./lbs. (2.8 nm)	blue	yes
Water Bottle Screws	20 in./lbs. (2.3 nm)	No	yes

*procedure for Fox, Maverick or pro shop only!
 ** One drop only - do not over apply! Use only if fastener is removed.